

**DYNO BATTERY, INC. FOUNDED 1933**

# Battery Spec Sheet 2VL16

*The bitterness of poor quality  
is long remembered after the  
fleeting thrill of a cheap price.*



L16



L16



Wing Nut



Marine Terminal



L16

## 2V Deep Cycle L16-2V

### Standard Specifications:

### L-16-2V

<b>Color Cover/Case:</b>	Blue /Black
<b>Case Material:</b>	Structural Foam
<b>Amp Hr Capacity:</b>	1050@20Hour Rate
<b>CCA</b>	Deep Cycle
<b>Reserve Capacity:</b>	630 Min @ 75 Amp Draw
<b>Plates per Cell:</b>	19
<b>Plate Thickness:</b>	POS .140 NEG .105
<b>Weight:</b>	LBS 118 KGS 54
<b>Default Terminal:</b>	#2 Utility Post

### Special Notes:

- 1) Optional Terminals: #3 Wing Nut or #4 Marine Flag
- 2) Rope handle included as standard.

### Battery Dimensions:

	Length	Width	Height
<b>English</b>	<b>12 3/8"</b>	<b>7 1/8"</b>	<b>16 3/4"</b>
<b>Metric</b>	<b>314 mm</b>	<b>181 mm</b>	<b>425 mm</b>

	<u>Per Std Pallet</u>	<u>Per Euro Pallet</u>
<b>Qty</b>	36	24
<b>Weight Lbs:</b>	4319	2891
<b>Weight KG's:</b>	1961	1313
<b>Configured</b>	2 layers of 18	2 layers of 12

Dyno Battery, Inc.  
4248-23 Ave W  
Seattle, Washington 98199  
USA  
PH: 206-283-7450  
FX: 206-283-7498  
www.dynobattery.com

# Dyno