

DYNO BATTERY, INC. FOUNDED 1933

Battery Spec Sheet L16

*The bitterness of poor quality
is long remembered after the
fleeting thrill of a cheap price.*



6V Deep Cycle D350

Standard Specifications:

Color Cover/Case:	Black /Black	<u>D-350</u>	<u>D-350HC</u>
Case Material:	Structural Foam		Available Soon
Amp Hr Capacity:	350 @20 Hour Rate		
CCA	Deep Cycle		
Reserve Capacity:	210 Min @ 75 Amp Draw		
Plates per Cell:	19		
Plate Thickness:	POS .140 NEG .105		
Weight:	LBS 118 KGS 54		
Default Terminal:	#2 Utility Post		

Special Notes:

- 1) Optional Terminals: #3 Wing Nut or #4 Marine Flag
- 2) Rope handle included as standard.

Battery Dimensions:

	Length	Width	Height
English	12 3/8"	7 1/8"	16 3/4"
Metric	314 mm	181 mm	425 mm

Packaging:

	<u>Per Std Pallet</u>	<u>Per Euro Pallet</u>
Qty	36	24
Weight Lbs:	4319	2891
Weight KG's:	1961	1313
Configured	2 layers of 18	2 layers of 12

Dyno Battery, Inc.
4248-23 Ave W
Seattle, Washington 98199
USA
PH: 206-283-7450
FX: 206-283-7498
www.dynobattery.com

Dyno