


DYNO BATTERY, INC. FOUNDED 1933

Battery Spec Sheet GC2

*The bitterness of poor quality
is long remembered after the
fleeting thrill of a cheap price.*



Dyno Battery, Inc.
4248-23 Ave W
Seattle, Washington 98199
USA
PH: 206-283-7450
FX: 206-283-7498
www.dynobattery.com

6V Deep Cycle D-105, D-125

<u>Standard Specifications:</u>	<u>D105(GC2c)</u>	<u>D125(GC2b)</u>
Color (cover/ case):	Black /Black	Black/Black
Case Material:	Polypropylene	Polypropylene
Amp 20Hr Capacity:	225	235
CCA	Deep Cycle	Deep Cycle
Reserve Capacity:	105 Min@75A	125Min@75A
Plates per Cell:	17	19
Plate Thickness (Pos/Neg):	.105/.085	.105/.085
Weight:	61# /28Kg	67#/30Kg
Default Terminal:	#2 Utility Post	

Special Notes: Cover includes integral bracket for carrying strap
1) Optional Terminals: #3 Wing Nut
2) Quick release vent caps available

Battery Dimensions:

	Length	Width	Height
English	10 5/16"	7 1/16"	10 7/8"
Metric	262 mm	179 mm	276 mm

	<u>D105/GC2c</u>	<u>D125/GC2b</u>
<u>Palletization:</u>	<u>Std Pallet/Euro</u>	<u>Std Pallet/Euro</u>
Qty	72 / 48	66 / 48
Weight Lbs:	4427/ 2963	4457 / 3251
Weight KG's:	2009 / 1345	2023 / 1476
Configured 3 layers of:	24 / 16	24 / 16