



Standard Specifications

Container Tray:	High Impact Polyethylene
Individual Cell Jar:	High Impact Polypropylene
AMP Hr Capacity:	600 at 6 Hour Rate
Electrolyte Reserve:	2+ inches above plates
Specific Gravity:	1.280
Plate Thickness:	.250 / .175
Plate Wrapping:	Glass Mat Envelopes
Separation Material:	Micro-Porous Polyethylene
Weight:	96 lbs / 43 kg

Battery Dimensions

English:	9 1/2" x 6 1/4" x 17 1/2"
Metric:	241mm x 159mm x 445mm

Special Notes

Innercell interlocking connectors
Quick release vent caps available

Cell Height 15"

Model	Cell Length	AH at 6 Hr	AH at 20 Hr
D50-05	2.00"	100	120
D50-07	2.75"	150	180
D50-09	3.50"	200	240
D50-11	4.25"	250	300
D50-13	5.00"	300	360
D50-15	5.75"	350	420
D50-17	6.50"	400	480
D50-19	7.25"	450	540
D50-21	8.00"	500	600
D50-23	8.75"	550	660
D50-25	9.50"	600	720
D50-27	10.25"	650	780
D50-29	11.00"	700	840

Cell Height 17"

Model	Cell Length	AH at 6 Hr	AH at 20 Hr
D65-05	2.00"	130	156
D65-07	2.75"	195	234
D65-09	3.50"	260	312
D65-11	4.25"	326	390
D65-13	5.00"	390	468
D65-15	5.75"	455	546
D65-17	6.50"	520	624
D65-19	7.25"	585	702
D65-21	8.00"	650	780
D65-23	8.75"	715	858
D65-25	9.50"	780	936
D65-27	10.25"	845	1,014
D65-29	11.00"	910	1,092

Cell Height 21"

Model	Cell Length	AH at 6 Hr	AH at 20 Hr
D85-05	2.00"	170	204
D85-07	2.75"	255	306
D85-09	3.50"	340	408
D85-11	4.25"	425	510
D85-13	5.00"	510	612
D85-15	5.75"	595	714
D85-17	6.50"	680	816
D85-19	7.25"	765	918
D85-21	8.00"	850	1,020
D85-23	8.75"	935	1,122
D85-25	9.50"	1,020	1,224
D85-27	10.25"	1,105	1,326
D85-29	11.00"	1,190	1,428

Cell Height 29"

Model	Cell Length	AH at 6 Hr	AH at 20 Hr
D120-05	2.00"	240	288
D120-07	2.75"	360	432
D120-09	3.50"	480	576
D120-11	4.25"	600	720
D120-13	5.00"	720	864
D120-15	5.75"	840	1,008
D120-17	6.50"	960	1,152
D120-19	7.25"	1,080	1,296
D120-21	8.00"	1,200	1,440
D120-23	8.75"	1,320	1,584
D120-25	9.50"	1,440	1,728
D120-27	10.25"	1,560	1,872
D120-29	11.00"	1,680	2,016

*Available Industrial 2 volt Cells. All 6.25" Wide.